

## PICOTE MINI MILLER

Easy to Move, Hard to Beat



The Mini Miller is a high speed, high torque unit designed for cleaning, descaling, and removing roots in pipes between DN50-100 (2-4") pipes and for cutting/reinstatements in DN50-75 (2-3") pipe. When paired with the Picote Mini Coating Pump it is capable of brush coating in DN50-150 (2-6") pipes as well.

Weighing only 27kg (60lbs), it's 8mm ( $\frac{1}{3}$ ") shaft has a reach of 16m (50'), which can be extended 10m (33') by adding a shaft extension.

It is fed by a standard 3 prong wall outlet making it a very easy to use on almost any jobsite\*.

## **USES AND BENEFITS**

- Designed to take up as little space as possible while covering a large range of applications.
- Time is money and the lightweight Mini Miller takes less time to transport and maneuver into position on jobsites.
- High Speed/High Torque: 500-2900 rpm.
- Lightweight: 27kg (60lbs)
- standard safety features include: safety clutch, in-line GFI\*\*, protective outer shaft casing, and an E-stop help to keep you and your equipment investment protected.
- Mini Cleaner +C camera upgrade available.

Technical Specifications	
Pipe Size Ranges	
Cleaning / Descaling	DN50-100 (2-4")
Cutting / Reinstatement	DN50-75 (2-3")
Picote Brush Coating™	DN50-150 (2-6")
Usable Shaft Length	16m (50')
Cable Extensions	10m (32 ft)
Shaft Size	8mm (1/3")
Casing Type	Thick
Output Power (Watts)	1100W
Speed (RPM)	500-2900
Power	UK/US: 110/125V, 15 Amp EU: 220/230V, 16 Amp
Weight	27kg (60 lbs)
Size	740 x 519 x 404mm 29 x 20 x16"
Safety Features	Protective shaft casing, operator presence foot control, in-line GFI**, manual safety clutch, & emergency stop.









<sup>\*</sup>Use with 110V / 16 Amp transformer in UK \*\*US model



## More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Mini Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

## **PRODUCTS AND SPARE PARTS**

Products and Parts	
PN	Description
3540000817	Mini Miller
3540000817US	Mini Miller 110v (US)
Spare Parts	
1312030085017	Mini Miller - 8mm (⅓") Shaft with Thick Casing 17.4m
9331008000	Thick outer casing for 8mm (½") shaft
900000856	Micro/Mini Miller Safety Clutch
900000920	Silicone Spring for Micro/Mini Miller (5 pcs)
9530000041	Safety Clutch Upgrade Kit for Micro/Mini Miller
9530000134	Strain Relief Micro/Mini Miller 9/13mm casing
9530000134-1	Strain Relief Spring Micro/Mini Miller for Safety Clutch
9530000045	Micro/Mini Miller Handle Upgrade Kit
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 liters/17oz)
1350000021	Picote Flexible Shaft Lubricant package (6 bottles)









**#GOPICOTE**